

Features:

- 1/3.2" progressive scan CMOS
- Dual streams from H.264 and MJPEG
- Up to 20 fps at 2048 x 1536
- Vandal resistance (IK10+)
- Ingress protection (IP67)
- Motorized varifocal lens for remote focus/zoom adjustment
- 3-axis mechanism (pan / tilt / roll)
- Removable IR-cut filter for Day/Night function
- High power IR LEDs
- Intelligent IR
- IR distance up to 20 m (65.6 ft.)
- External microphone
- 2-way audio
- One sensor input and alarm output
- TV-out support
- Built-in micro SD card slot (SD/SDHC) for local storage
- DC12V / AC24V / PoE+ (IEEE 802.3at)
- Wide Dynamic Range Pro (WDR Pro)
- 2D noise reduction
- Defog
- Motion detection
- Tampering alarm
- Privacy mask
- IP address filtering
- Supports iPhone, iPad, Android & 3GPP
- 31 languages on Web interface
- ONVIF (Profile S) conformant

Model Options:

ILS3MPRZ

3MP Camera w/ 3x Zoom, w/ OnVif Driver

*No License included to 3rd Party VMS

ILS3MPRZ-V3

3MP Camera w/ 3x Zoom, w/ ILS V3 Firmware

*Includes ILS VMS Perpetual License



Specifications:

CONNECTORS

Power	2-pin terminal block, PoE
Ethernet	Ethernet (10/100 Base-T), RJ-45 cable
Audio	1 In (3.5mm phone jack for microphone) 1 Out (3.5mm phone jack for speaker)
Digital I/O	3-pin terminal block, pitch 2.5 mm (0.1")
Local Storage	Micro SD card slot (SD/SDHC, SD version 2.0 only, Class 10) *SDXC and UHS-I card types are not supported.
TV-Out	BNC connector (640 x 480 resolution)
LED Indicator	2 LEDs: Power, Status

GENERAL

Environment Temperature	-20°C ~ 50°C (-4°F ~ 122°F)
Humidity	10% to 90% (no condensation)
Power Source	12V DC / 24V AC / PoE+ (IEEE 802.3at)
Max. Power Consumption	22.48 W
Dimensions (Camera Body)	ø 176.5 x 118 mm (6.9" x 4.6")
Weight	1.83 kg (4.03 lb)
Ingress Protection	IP67
Vandal Resistance	IK10+
Regulatory	CE, FCC, RCM, RoHS compliant

POWER OVER ETHERNET

PoE Standard	PoE+ (IEEE 802.3at Power over Ethernet / PD)
PoE Power Supply Type	End-Span
PoE Power Output	Per Port 48V DC, 600 mA, Max. 30W